

# GME-ST400 36V 25A



8 HOUR STANDARD CHARGE: 192 Ah BATTERY  
IDEAL FOR BATTERIES: 160 - 250 Ah

(SUITABLE FOR BATTERIES: 50 - 270 Ah)

**GM Electric Single Phase High Frequency Battery Charger ideal for 36 Volt Gel, AGM or Lead-Acid Batteries with 160 – 250Ah capacities.**

- Single-phase power supply voltage 230Vac  $\pm 10\%$  50-60Hz
- Supplied with AC 10A Single Phase 3 Flat Pin Plug
- Optional Anderson or REMA DIN DC plugs available for installation
- Max Input Current: 7.7 Amps
- Max Input Power: 1,242 W
- Max Output Power: 1,080 W
- Switching technology
- Charging curves settable via dip-switch for lead-acid, gel, AGM and lithium batteries (optional)
- Charging parameters modifiable via dip-switch
- Automatic start
- Current control precision  $\pm 1A$
- Voltage control precision  $\pm 0.1V$
- Efficiency  $\geq 90\%$
- Charging process managed by microprocessor
- Forced ventilation
- Clear and recognizable display of the charging process and alarms
- Thermal protection with internal probe
- Battery polarity inversion protection
- Charging interruption when battery is disconnected
- Possibility of on-board assembly with battery indicator bulb with LED (LED indicator bulb optional)
- Machine lock relay
- Dimensions: 300 x 170 x 75 mm
- Weight: 2 Kg

0413 015 775

[hello@forkliftbatterychargersdirect.com.au](mailto:hello@forkliftbatterychargersdirect.com.au)

[www.forkliftbatterychargersdirect.com.au](http://www.forkliftbatterychargersdirect.com.au)

